



BW 4 PART BRASS CABLE GLAND

Specification:

Size	20 mm to 90 mm S & L
Standard	BS 6121 PT1
Application	Dry Indoor, for use with all types of SWA Cable
Function	Provide mechanical Cable Retention & Electrical Wire continuity via Armored Wire.
Material	Brass BS 2874 CZ121 Pb3,CW614n,CW617n
Optional Threads	METRIC, NPT, BSP, PG or as specified
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified
Operating Temp.	-800 C to +3000 C
Accessories	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tag, Reducers, Adaptors, etc. as per the requirement



Technical Data:

Size	Thread	Length	A	B	A/F	A/C
20S	M20	10.00	13.00	18.00	23.50	26.00
20L	M20	10.00	14.00	21.00	25.00	28.00
25S	M25	10.00	18.00	24.00	31.00	35.50
25L	M25	10.00	20.50	27.00	33.00	37.00
32S	M32	10.00	27.00	33.50	40.50	45.50
32L	M32	10.00	27.00	33.50	40.50	45.50
40S	M40	13.00	31.50	39.50	45.50	50.50
40L	M40	13.00	33.00	41.50	49.00	55.00
50S	M50	13.00	39.50	48.50	56.50	63.50
50L	M50	13.00	44.50	54.50	62.50	70.50
63S	M63	14.00	50.20	59.20	68.80	77.00
63L	M63	13.50	56.50	65.50	76.00	86.00
75S	M75	15.00	63.50	72.00	84.00	94.50
75L	M75	15.00	69.50	78.50	90.00	101.00



Size	Thread	Length	A	B	A/F	A/C
90S	M90	20.00	76.00	85.00	100.00	111.20
90L	M90	18.00	78.40	90.50	103.00	115.00

Also available in Kit Packaging and also as per the specification.