



E1W TYPE BRASS CABLE GLAND

Specification:

Size	20 mm to 90 mm S & L
Standard	EN 50262 : 1999
Application	For indoor or outdoor use with all types of SWA Cable
Function	Provide for Environmental Seal in the Cable Outer sheath. Also, provide mechanical cable retention & electrical continuity
Material	Brass BS 2874 CZ121 Pb3, CW614n,CW617n
Optional Threads	METRIC, NPT, BSP, PG or as specified
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified
Operating Temp.	Standard seals -200 C to +800 C
Accessories	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tag, Reducers, Adaptors, etc. as per the requirement



Technical Data:

Size	Thread	Length	A	B	A/F	A/C
20S	M20	15.00	12.00	16.00	22.20	24.20
20L	M20	15.00	14.00	20.50	27.00	29.50
20/16	M20	15.00	9.00	14.00	22.20	24.20
25S	M25	15.00	18.50	24.50	33.50	37.50
25L	M25	15.00	20.50	27.50	36.00	40.00
32S	M32	10.40	24.30	34.00	43.00	48.50
32L	M32	15.00	26.27	34.20	43.50	48.50
40S	M40	15.00	29.50	41.50	52.00	58.00
40L	M40	15.00	33.00	41.50	52.00	58.00



Size	Thread	Length	A	B	A/F	A/C
50S	M50	15.00	38.50	47.00	59.00	65.50
50L	M50	15.00	44.30	53.20	64.20	71.50
63S	M63	20.00	50.20	62.50	73.50	81.50
63L	M63	20.00	56.20	65.50	79.50	89.00
75S	M75	20.00	62.00	74.00	87.00	97.00
75L	M75	20.00	68.00	78.20	97.00	108.00
90L	M90	18.50	80.00	91.00	103.50	114.50

Also available in Kit Packaging and also as per the specification.