



IP 68 CABLE GLAND

Specification:

Item Brass IP68 Universal Cable Gland

Technical Information	Material
Body with Lock Nuts	Nickel Plated Brass
Insert	Polyamide - 6
Sealing Ring	Neoprene
O - Ring	Perbunan

Additional Features :

- With Vibration Lock and Strain Relief Protection Class IP 68 - 5 Bar
- Temperature Range : -3000 to +9000 C



Technical Data:

Size	Clamping Range	Thread Length (in mm)
PG-7	2-6.50	6.00
PG-9	3-8.00	6.00
PG-11	4-10.00	6.00
PG-13.5	5-12.00	8.00
PG-16	8-14.00	8.00
PG-21	11-18.00	8.00
PG-29	16-25.00	9.00
PG-36	20-30.00	9.00
PG-42	28-38.00	12.00



PG-48	34-44.00	12.00
M12	2-6.50	6.00
M16	3-8.00	6.00
M20	5-12.00	8.00
M25	11-18.00	8.00
M32	12-21.00	8.00
M40	18-27.00	9.00
M50	27-33.00	9.00
M63	34-48.00	12.00



Cable Glands are suitable for connections provides with flexible cables in:

- Weather Proof Enclosures
- Control Panels
- Limit Switches
- Multi Pin Connectors
- Controlling & Liquid Measuring Instrument
- Machineries
- Medical Equipments
- Electric Motors

We manufacture other types of Accessories also and according to specifications, drawing and samples. Other Accessories like Cable Ties, Reducers, Enlargers, Adaptors, Converters, Stopping Plugs.