



PG Cable Glands with IP-65 Protection

Specification:

Size	PG 7 to PG 48
Standard	EN 50262 : 1999
Application	Outdoor or Indoor for use with all types of Unarmoured Cable
Function	Provide Seal on Outer Sheath of the Unarmoured Cable
Ingress Protection	IP65
Material	Brass BS 2874 CZ121 Pb3, CW614n, CW617n
Finish	Chrome Finish, Brass Finish, Nickel Finish or as specified
Thread	PG and also available in Metric Threads on request
Seals	Neoprene Material
Operating Temp.	-200 C to +800 C
Accessories	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tags, Reducers, Adaptors, etc. as per the requirement



Technical Data:

Size	A	B	C	D	E	F	G
PG-7	14.00	15.50	20.50	PG-7	10.00	5.00	150
PG-9	18.00	20.00	23.50	PG-9	12.50	6.00	150
PG-11	20.00	22.00	26.50	PG-11	15.00	6.50	150
PG-13	23.00	25.00	27.00	PG-13	16.75	7.10	150
PG-16	25.00	27.80	28.00	PG-16	18.50	6.50	150
PG-21	31.00	34.00	31.00	PG-21	24.10	7.10	150
PG-29	41.50	45.20	34.00	PG-29	32.10	8.50	150
PG-36	51.00	56.50	40.00	PG-36	43.00	10.00	150
PG-42	58.50	63.75	43.00	PG-42	47.50	10.00	150
PG-48	64.00	70.50	47.00	PG-48	52.25	10.00	150

Also available in Kit Packaging and also as per the specification.